



iCon 125kW/261kWh C&I Liquid-Cooled ESS

SU261E125LM

Highly Integrated

All-in-One design,
covering an area of 1.6m²,
saving 25% space.

Safe and Reliable

Nine-layer safety protection
and certifications spanning Cell,
Pack, Cluster and System.

Smart O&M

Risen Cloud provides real-time alarm
and troubleshooting solution.



Technical Specification

System Model	SU261E125LM
System Information	
Rated AC Power	125kW
Rated Capacity	261kWh
Battery Information	
Cell Type	LFP
Cell Capacity	314Ah
Configuration	260S1P
Rated Voltage	832V
Voltage Range	728 ~ 949V
Charge & Discharge Rate	0.5C
Depth of Discharge (DoD)	98%
PCS	
AC Power	125kW
Operating Mode	On-grid & Off-grid
Rated Grid/Islanded Voltage	400Vac
Power Factor	1.0 leading~1.0 lagging
Rated Grid Frequency	50Hz
Connection Type	3P4L
Operating Environment	
Protection Degree	IP55
Noise	75dB
Operating Temperature Range	-30°C~55°C (>45°C Derating)
Relative Humidity	0~95%
Max. Operating Altitude	3000m (>2000m Derating)
Anti-Corrosion Degree	C3(C5 Optional)
Specifications	
Dimensions(WxHxD)	1050x2450x1520mm
Weight	2.6t
Cooling Type	Intelligent Liquid Cooling
Design Lifetime	10 years
Fire Suppression System	Aerosol+Water
Communication Protocol	CAN/RS485
Certifications	IEC

SYL(Ningbo)Battery Co.,Ltd.